

AD FLAT



TECHNICAL SPECIFICATIONS :

Parallelepiped, polyethylene tank suitable for AdBlue storing, complete with:

- nr° 1" bottom draining point with cap;
- nr° 1" connection with 1" ball valve in polyethylene for unit pump connection;
- nr° 4 x 2" connections on tank upper part with cover cap

BOX MOUNTED PUMP UNIT for Ad Blue :

Metallic box unit made of epoxy coated carbon steel sheet with lockable door complete with :

- 1" PVC suction line;
- Electro motor vane pump, with , flow rate: 40 LPM, prevalence: m. 4, complete with "schuko type" plug and non-return valve;
- Digital display flow meter with oval gear, model K 24, suitable for Ad Blue, high accuracy (0.5%);
- 5 m. hose length with pressure couplings;
- Automatic nozzle, PIUSI model, with stainless steel parts suitable for Ad Blue dispensing.

OPTIONAL :

- 2" Stainless steel filling line with Mann Tek coupling.
- Heating system for box mounted pump unit
- Pneumatic Level probe, "OCIO"
- Spring driven automatic hose reels, 8m.



MODEL	CAPACITY (LT.)	DIMENSIONS (MM)	FLOW RATE
AD FLAT 15 - 5K	1.500	2.320 x 720 x h. 1.650	30 lt./min. - 240 V.
AD FLAT 20 - 5K	2.000	2.930 x 720 x h. 1.650	30 lt./min. - 240 V.
AD FLAT 50 - 5K	4.860	2.390 x 1.350 x h. 1.980	30 lt./min. - 240 V.

